

SERVER CABINET 6580



FEATURES

- Overall compact size of 600 mm wide by 600 mm deep (Frame to Frame = 580 mm)
- Space saving flat pack shipping.
- Easily assembled on site
- Lockable door and side panels for system security
- Fully adjustable vertical mounting rails
- Expandable with wide range of options
- U numbers printed on rails
- Static Load Rating : 1000kg.
- Heavy Duty Caster rated to 250kg. per caster

Heights :

15U, 27U, 39U, 42U and 45U

Standard :

Conforms to EIA-310D Type A, IEC-60297-2

Material :

High grade cold rolled steel
All materials comply to RoHS standard

Finish :

5 stage iron phosphate pretreatment followed by tough scratch resistant powder coat paint

Color :

Low Gloss Black

SPEC SHEET MODEL 6580

Application

The Cyberack 6580 is an ideal light network rack. The 6580 is a space saver which accepts a variety of equipment not requiring full depth. The 600 mm depth will install numerous routers, switches and light networking devices and still allow ample room for cable management at the rear of the cabinet. The compact design, ease of assembly, and low cost of ownership makes the 6580 perfect for both the small office environment, and its sturdy features and compliance to international standards allows the 6580 to fit into any IT manager's plan.

Internal Useable Height (mm)

UNIT REF.	A	B
27U	1375	1203
39U	1908	1736
42U	2042	1870
45U	2175	2003

600W	C	D	E
	600	465	450

Depth	F	G	H	I
600D	649	580	466	431
800D	869	800	686	531
900D	969	900	766	631
1000D	1069	1000	866	731

1U = 44.45mm / 1.75 in.

