

SERVER CABINET 6900



FEATURES

- Depth of 900 mm
- Enhanced thermal management capabilities
- Improved cable management support
- Easily expandable on site
- Field reversible lockable doors
- Caster rated 250 kg/wheel
- Static Load Rating : 1000kg.
- U numbers printed on rails.

Heights :

27U, 39U, 42U and 45U

Standard :

Conforms to EIA-310D Type A, IEC-60297-2

Material :

High grade cold rolled steel
All materials comply to RoHS standard

Finish :

5 stage iron phosphate pretreatment followed
by tough scratch resistant powder coat paint

Color :

Low Gloss Black

SPEC SHEET MODEL 6900

The Cyberack 6900 provides a solution for those unable to fit 1000 mm deep cabinets into their site, but who need more than 800 mm depth. The additional depth, 900 mm standard, will house many of today's deep servers. Thermal management is another crucial feature in today's rack mount environment, and Cyberack 6900 can be fitted with a range of door and roof options to satisfy your particular configuration.

Internal Useable Height (mm)

UNIT REF.	A	B
27U	1375	1203
39U	1908	1736
42U	2042	1870
45U	2175	2003

600W	C	D	E
	600	465	450

Depth	F	G	H	I
600D	649	580	466	431
800D	869	800	666	531
900D	969	900	766	631
1000D	1069	1000	866	731

1U = 44.45mm / 1.75 in.

