

NETWORKING CABINET 81000



FEATURES

- Ideal for mixed equipment installations
- Array of doors to achieve proper thermal management
- Economized space usage by accepting both rack mounted and free standing equipment
- Secure environment
- Extensive work space for cable management.
- Static Load Rating: 1000kg
- Heavy Duty Caster rated to 250kg per caster

Heights :
27U, 39U, 42U and 45U

Standard :
Conforms to EIA-310D Type A, IEC-60297-2

Material :
High grade cold rolled steel
All materials comply to ROHS standard

Finish :
5 stage iron phosphate pretreatment
followed by tough scratch resistant powder
coat paint

Color :
Low gloss black

SPEC SHEET MODEL 81000

Application

The Cyberack 81000 was engineered to meet the demands of both high density server installation plus network management requirements. The overall depth of 1000 mm will accept the most deep rack mounted servers on the market. Additional depth can be added on request. A wide selection of doors and other accessories rounds out the solutions offered by Cyberack 81000.

Internal Useable Height (mm)

UNIT REF.	A	B
27U	1375	1203
39U	1908	1736
42U	2042	1870
45U	2175	2003

800W	C	D	E
	800	465	450

Depth	F	G	H	I
800D	869	800	866	531
900D	969	900	766	631
1000D	1069	1000	866	731

1U=44.45mm / 1.75in.

